



Subprograms: Local Variables

ICS312 Machine-Level and Systems Programming

Henri Casanova (henric@hawaii.edu)



Local Variables in Subprograms

- In all the examples we have seen so far, the subprograms were able to do their work using only registers
- But sometimes, a subprogram's needs are beyond the set of available registers and some data must be kept in memory
 - Just think of all subprograms you wrote that used more than 6 local variables (EAX, EBX, ECX, EDX, ESI, EDI)
- One possibility could be to declare a small `.bss` segment for each subprogram, to reserve memory space for all local variables
- Drawback #1: memory waste
 - This reserved memory consumes memory space for the entire duration of the execution even if the subprogram is only active for a tiny fraction of the execution time (or never!)
- Drawback #2: subprograms are not reentrant

Re-entrant subprogram

- A subprogram is **active** if it has been called but the RET instruction hasn't been executed yet
- A subprogram is **reentrant** if it can be called from anywhere in the program
- This implies that the program can call itself, directly or indirectly, which enables recursion
 - e.g., f calls g, which calls h, which calls f
- At a given time, two or more instances of a subprogram can be active
 - Two or more activation records for this subprogram on the stack
- **If we store the local variables of a subprogram in the .bss segment, then there can only be one activation!**
 - Otherwise activation #2 could corrupt the local variables of the activation #1
- Therefore, with our current scheme for storing local variables, programs are not reentrant and one cannot have recursive calls when subprograms have local variables!
 - In our previous example the recursive program had no local variables, so we were "lucky"
- Having reentrant programs is so useful that we don't want to live without it

Local variables on the stack

- Since activation records on the stack are used to store relevant information pertaining to a subprogram, why not use them for storing the subprogram local variables?
- **The standard approach is to store local variables right after the saved EBP value on the stack**
 - This is simply done by subtracting some amount to the ESP pointer
- The local variables are then accessed as $[\text{EBP} - 4]$, $[\text{EBP} - 8]$, etc.
- Let's see this on an example

Local Variable Examples

- Say we have a subprogram that takes 2 parameters, uses 3 local variables, and doesn't return any value
- The code of the subprogram is as follows:

func:

```
push    ebp           ; save old EBP value
mov     ebp, esp      ; set EBP
sub     esp, 12       ; add space for 3 local variables
; subprogram body
mov     esp, ebp      ; deallocate local variables
pop     ebp           ; restore old EBP value
ret
```

- Let's look at the stack when the subprogram body begins

Local Variables Example

- Inside the body of the subprogram, parameters are referenced as:

- [EBP+8]: 1st parameter
- [EBP+12]: 2nd parameter

- Inside the body of the subprogram, local variables are referenced as:

- [EBP-4]: 1st local variable
- [EBP-8]: 2nd local variable
- [EBP-12]: 3rd local variable

EBP+12	2nd parameter
EBP+8	1st parameter
EBP+4	return address
EBP	saved EBP
EBP-4	1st local var
EBP-8	2nd local var
EBP-12	3rd local var

Local Variables Example

- Inside the body of the subprogram, parameters are referenced as:

- [EBP+8]: 1st parameter
- [EBP+12]: 2nd parameter

- Inside the body of the subprogram, local variables are referenced as:

- [EBP-4]: 1st local variable
- [EBP-8]: 2nd local variable
- [EBP-12]: 3rd local variable


EBP+12	2nd parameter
EBP+8	1st parameter
EBP+4	return address
EBP	saved EBP
EBP-4	1st local var
EBP-8	2nd local var
EBP-12	3rd local var

Very important you have this picture in mind; you should be able to redraw it


A “deep” stack

- Each call to a subprogram puts an activation record on the stack, saved EBP values and arguments
- **Important:** While a function is active, EBP always points to the saved EBP value saved for the function’s caller
 - EBP is sort of the anchor point of the activation record (“B” stands for **Base** Pointer)
- We have seen this on a small example in the previous set of lecture notes
- Let’s look at a bigger example
 - But not with the corresponding assembly code


x() calls e() calls f() calls g() calls h()




x() calls e() calls f() calls g() calls h()




x() calls e() calls f() calls g() calls h()



x() calls e() calls f() calls g() calls h()




x() calls e() calls f() calls g() calls h()




- The saved EBPs provide links between the activation records
- The current EBP is for the current function
- Let's see what happens when h returns

x() calls e() calls f() calls g() calls h()




- When h returns
 - `mov ESP, EBP`

x() calls e() calls f() calls g() calls h()




x() calls e() calls f() calls g() calls h()



- When h returns
 - mov ESP, EBP
 - pop EBP
 - pop return address

x() calls e() calls f() calls g() calls h()



- We are now in a “clean” state, where g is the active subprogram
- The EBP register and its saved values provide the crucial link between activation records
- If EBP values get corrupted, then all is lost

ENTER and LEAVE

- We always have the same *prologue* and the same *epilogue*

```
push    ebp           ; save old EBP value
mov     ebp, esp      ; set EBP
sub     esp, X        ; reserve X=4*N bytes for N local vars
```

```
mov     esp, ebp      ; remove space for local vars
pop     ebp           ; restore old EBP value
ret
```

ENTER and LEAVE

- There are two convenient functions: ENTER and LEAVE

```
push  ebp           ; save old EBP value
mov   ebp, esp      ; set EBP
sub   esp, X        ; reserve X=4*N bytes for N local vars
```

equivalent to

```
enter  X, 0
```

```
mov   esp, ebp     ; remove space for local vars
pop   ebp          ; restore old EBP value
ret
```

equivalent to

```
leave
ret
```

Recall the NASM Skeleton

; include directives

segment .data

; DX directives

segment .bss

; RESX directives

segment .text

global asm_main

asm_main:

enter 0,0

pusha

; Your program here


popa

mov eax, 0

leave

ret

Prologue and epilogue of asm_main



We Finally Understand the Skeleton

```
; include directives
```

```
segment .data
```

```
; DX directives
```

```
segment .bss
```

```
; RESX directives
```

```
segment .text
```

```
    global asm_main
```

```
asm_main:
```

```
    enter    0,0                ; Save EBP, reserve 0 bytes for local variables
```

```
    pusha                    ; Save ALL registers
```

```
    ; Your program here
```

```
    popa                    ; Restore ALL registers
```

```
    mov     eax, 0            ; Set the return value to 0
```

```
    leave                   ; Restore EBP, remove space for local variables
```

```
    ret                      ; Pop the return address and jump to it
```



Knowing your stack

- At this point it should be clear that it is very important to understand how the stack works and how to use it
- When programming in assembly you should always have a mental picture of the stack
 - Something you don't do when using a high-level programming language typically
 - As always, abstractions are great, but having no idea how they are implemented can be problematic when hunting bugs
 - Basic example: “running out of stack space”
- It's typically a good idea to be consistent
 - Compilers are consistent by design

A Full Example

- Let's write the assembly code equivalent to the following C/Java function

```
int f(int num) { // computes Fibonacci numbers
    int x, sum;
    if (num == 0) return 0;
    if (num == 1) return 1;
    x = f(num-1);
    sum = x + f(num-2)
    return sum;
}
```

- Let's write a “straight” translation, without optimizing variables away, just for demonstration purposes

A Full Example (main program)

```
%include "asm_io.inc"
```

```
segment .data
```

```
msg1      db  "Enter n: ", 0  
msg2      db  "The result is: ", 0
```

```
... ; declaration of asm_main and setup
```

```
mov     eax, msg1      ; eax = address of msg1  
call    print_string   ; print msg1  
call    read_int       ; get an integer from the keyboard (in EAX)  
push   eax             ; put the integer on the stack (parameter #1)  
call    f              ; call f  
pop     ebx            ; remove the parameter from the stack  
mov     ebx, eax       ; save the value returned by f  
mov     eax, msg2     ; eax = address of msg2  
call    print_string   ; print msg2  
mov     eax, ebx       ; eax = sum  
call    print_int      ; print the sum  
call    print_nl       ; print a new line
```

```
... ; clean up
```


A Full Example (function f)

```
; FUNCTION: f
; Takes one parameter: an integer
; eax = return value
segment .text
f:  enter 8,0      ; num in [ebp+8]
                        ; local var x in [ebp-4],
                        ; local var sum in [ebp-8]

    push ebx      ; save ebx
    push ecx      ; save ecx
    push edx      ; save edx

    mov  eax, [ebp+8] ; eax = num
    sub  eax, 2      ; eax -= 2
    jns  next      ; if not <0, goto next
    add  eax, 2      ; eax += 2
    jmp  end

next:
    mov  eax, [ebp+8] ; eax = num
    add  eax, -1     ; eax -= 1
```

```
    push  eax      ; put (num -1) on stack
    call f         ; call f (recursively)
    add  esp, 4    ; remove (num-1) from stack
    mov  [ebp-4], eax ; put the returned value in x
    mov  eax, [ebp+8] ; eax = num
    add  eax, -2    ; eax -= 2
    push  eax      ; put (num -2) on stack
    call f         ; call f (recursively),
                        ; the return value is in eax
    add  esp, 4    ; remove (num-1) from stack
    add  eax, [ebp-4] ; eax += x

end:
    pop  edx      ; restore ebx
    pop  ecx      ; restore ecx
    pop  ebx      ; restore edx
    leave         ; clean up the stack
    ret          ; return
```

Interfacing Assembly and C

- Section 4.7 of the book talks about interfacing C and assembly
- We have seen most of this content already, but let's talk about the issue of saving registers on the stack
- By convention, C assumes that a subprogram (e.g., the one you're writing in assembly), will not destroy values in EBX, ESI, EDI, EBP, CS, DS, SS, and ES
- So, if you write an assembly subprogram, make sure you save these on the stack and restore them
 - We've already said we save EBP
- Example: I know my subprogram uses EBX (as on page 86)

```
enter    4,0           ; prologue (1 32-bit local var)
push    ebx           ; save EBX
...
pop ebx           ; restore EBX
leave           ; epilogue
ret           ; return
```



Conclusion

- When programming one always faces trade-offs between program readability and program performance
- With by-hand assembly programming, the programmer can make fine-tuned decisions for these trade-offs
 - e.g., for a particular function I decide to not save all registers because I know that it won't corrupt them, thus saving time
 - e.g., I know that I can reuse some register value that was modified in a subprogram to do some clever optimization
- Some of these optimizations can only be done by a human who understands what the program does
 - Many optimizations can be done by a compiler